

VESX45/PGS

Personnel Grounding Strap



Stainless steel VESX45/PGS Personnel Grounding Strap



Adjustable wrist strap with quick release connector

The VESX45/PGS is a medium duty stainless steel grounding clamp and wrist strap assembly that provides operators working in hazardous areas with an additional layer of protection against fires or explosions caused by static electricity.

Through their own movement people can generate large amounts of static charge if they are not grounded. In some cases, as much as 30,000 volts can be carried by people who are completely unaware that they themselves are the potential source for an electrostatic spark discharge that could ignite a flammable atmosphere.

If the operating requirements of certain processes cause the loss of direct contact between the operator's static dissipative safety shoes and the static dissipative flooring of the plant, the VESX45/PGS provides an added layer of protection to ensure the operator is grounded via the plant or bonded to the equipment they are interacting with.

For example, an operator may need to stand on a ladder to tip powder into a large mixer and in the process of moving to the ladder loses contact with the static dissipative flooring.

To ensure static cannot accumulate on the operator, by fastening the grounding strap to their wrist, any charge generated by their movement can be dissipated to ground by direct contact to a verified ground connection.

**refer to page 2 of this datasheet to see what IEC 60079-32-1 and NFPA 77 recommend with respect to the use of personnel grounding straps.*

Product Features

FM & ATEX approved medium duty stainless steel grounding clamp with tungsten carbide teeth mounted in a side-by-side configuration to provide a high degree of clamp stability and to bite through rust, coatings and deposits of process material.

12 ft (3.7 m) spiral cable fitted with a quick release connector enables operators to detach themselves in the event that they need to vacate the process area immediately.

1 Meg-Ohm safety resistor mounted in the cable to limit stray electrical currents passing through the operator.

Adjustable anti-allergy wrist strap to fit a wide range of wrist sizes.

VESX45/PGS

Technical Specification


VESX45/PGS

Clamp Details:	FM / ATEX approved medium duty static grounding clamp
Clamp Material:	Stainless handles (SS 304) and spring (SS 302) Tungsten carbide teeth for maximum penetration
Clamp Dimensions:	4.7" x 1.0" (120 mm x 25 mm) (length x width)
Clamp Jaw Opening:	0.6" (15 mm) maximum
Wrist Strap:	Anti-allergy adjustable strap
Electrical Safety Resistor:	1 Meg-Ohm resistor mounted in the conductor
Cable Details:	12 ft (3.7 m) single pole spiral conductor fitted to a quick release connector

Personnel Grounding Strap test kit is available on request.

Hazardous Location Approvals

Grounding Clamp

North America:	Europe / International Version Available:
FM approved	ATEX  ATEX Notified Body: SIR4

* Both section 11.4 of IEC 60079-32-1 and section 8.2.3.3 of NPFA 77 state the following:

"The simplest type of commercial device is an earthing bracelet with a built-in resistor typically giving a resistance to ground of about 100 kΩ for shock protection. Wrist straps of this type have the greatest utility at ventilation hoods and at other locations where limitation on the operator's mobility can be tolerated. Breakaway wrist tether systems could be necessary where emergency egress is needed. A hood can be equipped with two external coiled earthing cords with cuff attachments that can be removed and kept by individual users."

IEC 60097-32-1: Explosive atmospheres, Electrostatic Hazards, Guidance.

NPFA 77 "Recommended Practice on Static Electricity".

* Always check for and read the latest version of the International Standards and or Recommended Practices.

Copyright Notice

The website and its content is copyright of Newson Gale Ltd © 2020. All rights reserved.

Any redistribution or reproduction of part or all of the contents in any form is prohibited other than the following:

- you may print or download to a local hard disk extracts for your personal and noncommercial use only
- you may copy the content to individual third parties for their personal use, but only if you acknowledge the website as the source of the material

You may not, except with our express written permission, distribute or commercially exploit the content. Nor may you transmit it or store it in any other website or other form of electronic retrieval system.

Right to change

This document provides general information only and may be subject to change at any time without notice. All information, representations, links or other messages may be changed by Newson Gale at any time without prior notice or explanation.

Newson Gale is not obliged to remove any outdated information from its content or to expressly mark it as being outdated. Please seek the advice of professionals as necessary regarding the evaluation of any content.

Disclaimer of liability

The information provided in this Datasheet is provided by Newson Gale without any representations or warranties, expressed or implied, as to its accuracy or completeness. The liability of Newson Gale for any expenses, losses or actions incurred whatsoever by the recipient as a result of the use of this Datasheet shall be excluded.

Leading the way in hazardous area static control



www.newson-gale.com

2/2

United Kingdom
Newson Gale Ltd
 Omega House
 Private Road 8
 Colwick, Nottingham
 NG4 2JX, UK
 +44 (0)115 940 7500
 groundit@newson-gale.co.uk

United States
IEP Technologies LLC
 417-1 South Street
 Marlborough, MA 01752
 USA
 +1 732 961 7610
 groundit@newson-gale.com

Deutschland
IEP Technologies GmbH
 Kaiserswerther Str. 85C
 40878 Ratingen
 Germany
 +49 (0)2102 58890
 erdung@newson-gale.de